

DOW CORNING(R) PHARMA-50 TUBING**1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY**

Dow Corning Corporation
South Saginaw Road
Midland, Michigan 48686

24 Hour Emergency Telephone: (989) 496-5900
Customer Service: (989) 496-6000
Product Disposal Information: (989) 496-6315
CHEMTREC: (800) 424-9300

MSDS No.: 04007679

Revision Date: 2004/09/03

Generic Description: Silicone elastomer
Physical Form: Cured Elastomer
Color: Translucent-colorless to pale yellow
Odor: Not available

NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. OSHA HAZARDOUS COMPONENTS

This product is an "article" as defined in Federal OSHA Hazard Communication Rule 29 CFR 1910.1200, and does not require a material safety data sheet.

3. EFFECTS OF OVEREXPOSUREAcute Effects

Eye: Not applicable.

Skin: Not applicable.

Inhalation: Not applicable.

Oral: Not applicable.

Prolonged/Repeated Exposure Effects

Skin: No known applicable information.

Inhalation: No known applicable information.

Oral: No known applicable information.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology

DOW CORNING(R) PHARMA-50 TUBING

information.

4. FIRST AID MEASURES

Eye: Not applicable.

Skin: Not applicable.

Inhalation: Not applicable.

Oral: Not applicable.

Comments: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flash Point: Not applicable.

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.

Fire Fighting Measures: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Use water spray to keep fire exposed containers cool. Determine the need to evacuate or isolate the area according to your local emergency plan.

Unusual Fire Hazards: None.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Collect and contain for salvage or disposal. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See section 8 for Personal Protective Equipment for Spills. Call Dow Corning Corporation, (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation.

DOW CORNING(R) PHARMA-50 TUBING

Use reasonable care and store away from oxidizing materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Component Exposure Limits**

There are no components with workplace exposure limits.

Engineering Controls

Local Ventilation: Not applicable.
General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Not applicable.
Skin: Not applicable.
Suitable Gloves: Not applicable.
Inhalation: Not applicable.
Suitable Respirator: Not applicable.

Personal Protective Equipment for Spills

Eyes: Not applicable.
Skin: Not applicable.
Inhalation/Suitable Respirator: Not applicable.

Precautionary Measures: Use reasonable care.

Comments: When heated to temperatures above 150 degrees C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin, and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Cured Elastomer
Color: Translucent-colorless to pale yellow
Odor: Not available
Specific Gravity @ 25°C: 1.15

DOW CORNING(R) PHARMA-50 TUBING

Viscosity: Not determined.
Freezing/Melting Point: Not determined.
Boiling Point: Not determined.
Vapor Pressure @ 25°C: Not determined.
Vapor Density: Not determined.
Solubility in Water: Not determined.
pH: Not determined.
Volatile Content: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction.

11. TOXICOLOGICAL INFORMATION**Special Hazard Information on Components**

No known applicable information.

12. ECOLOGICAL INFORMATION**Environmental Fate and Distribution**

Air: This product is a solid consisting of a high molecular weight silicone polymer and other solid materials. Unless milled to produce a dust or particles, it is unlikely to give rise to atmospheric contamination.

Water: This product is a solid which is completely insoluble in water. As the specific gravity is >1, it will sink to the bottom of the water course.

Soil: This product will enter the terrestrial environment if, as a component of municipal or industrial solid waste the product is landfilled. It is unlikely that further significant transformation of the product will occur.

Degradation: High molecular weight polymer which is amenable to recycling. The product is not biodegradable. The product is removed >80% during the sewage treatment process.

Environmental Effects

Toxicity to Water Organisms: This product has low water solubility and should not present a risk to aquatic organisms.

DOW CORNING(R) PHARMA-50 TUBING

Toxicity to Soil Organisms: This product is a solid and does not contain significant concentrations of water soluble constituents that may be leached from the product. It is therefore not likely to present a danger to terrestrial organisms.

Bioaccumulation: This product is a solid which is not soluble in water and if ingested will not be absorbed.

Fate and Effects in Waste Water Treatment Plants

This product is a solid rubber type material which is unlikely to have any adverse effect on bacteria.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal.

Call Dow Corning Corporate Environmental Management, (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION**DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

DOW CORNING(R) PHARMA-50 TUBING**EPA SARA Title III Chemical Listings****Section 302 Extremely Hazardous Substances:**

None.

Section 304 CERCLA Hazardous Substances:

None.

Section 312 Hazard Class:Acute: No
Chronic: No
Fire: No
Pressure: No
Reactive: No**Section 313 Toxic Chemicals:**

None present or none present in regulated quantities.

Supplemental State Compliance Information**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

Massachusetts

No ingredient regulated by MA Right-to-Know Law present.

New Jersey

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
None	> 60.0	Cured rubber article

Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
None	> 60.0	Cured rubber article

DOW CORNING(R) PHARMA-50 TUBING**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark